

Specifications		eBOX-IV Series											
		eBOX-4800	eBOX-4800T	eBOX-4850	eBOX-4850T	eBOX-4851	eBOX-4851S	eBOX-4852	eBOX-4852S	eBOX-4853	eBOX-4853S	eBOX-4854	
System	Processor	VIA Eden Esther (1.2GHz) processor											
	BIOS	AMI BIOS											
	System Chipset	VIA CX700M											
	I/O Chip	VIA VT1211											
	System Memory	Onboard 512MB DDR2											
MIO	EIDE (UltraDMA133, 44Pin 2.0 Pitch)	X1											
	PS/2 K/B	X1											
	PS/2 Mouse	X1											
	PRT	N/A		X1		N/A		X1	N/A		X1	N/A	
	RS232	N/A		X2	X2	N/A		X1	N/A		X1	N/A	
I/O	USB	2 X USB 2.0 Ports (one at front)										6 X USB 2.0 Ports	
	Type I/II Compact Flash Slot	N/A				X1							
	Mini PCI socket	N/A				1 X Mini-PCI Socket					N/A		1 X Mini-PCI Socket
Output	VGA	TV / S-Video	VGA	TV / S-Video	VGA								
Display	Chipset	integrated VIA UniChrome Pro II, 2D/3D Graphics with MPEG4 and WMV9 decoding accelerator											
	Display Memory	Up to 64MB share system memory											
	Resolution	Up to 1920 x 1440											
Audio	AC97 2.2 (Codec)	VIA Vinyl VT1708											
	Audio Interface	Line out, Mic in											
Ethernet	Realtek RTL8100B 10/100 Base-T Ethernet	X1					X2					X1	
	Remote Boot ROM	built-in boot ROM function											
Optional	2.5" Hard Disk installation support	N/A		Yes				N/A		Yes		N/A	
	Wireless IEEE 802.11b/g	N/A				Optional				N/A		Optional	
Mechanical & Environment	Power Requirement	+5V @4A											
	Operating Temperature	0 ~ 60 °C ( 32-140 °F)											
	Size (W x H x D)	170 x 123 x 38 mm			170 x 123 x 56 mm								
	Weight	780g			970g								
	Certifications	CE, FCC											